

SV-65

Blow-off capacity without discharge pipe. Litres of cold water per minute at a 10% pressure increase.

SET PRESSURE MPa*	CAPACITY [ART.NO.**]					
	DN15	DN20	DN25	DN32	DN40	DN50
0.10	20 (5004011)	47 (5004029)	68 (5004047)	133 (5004065)	210 (5004083)	250 SV-65S-G50/G65-0100
0.20	28 (5004012)	67 (5004030)	92 (5004048)	150 (5004066)	250 (5004084)	290 SV-65S-G50/G65-0200
0.30	33 (5004013)	83 (5004031)	113 (5004049)	180 (5004067)	300 (5004085)	46 SV-65S-G50/G65-0300
0.40	35 (5004014)	95 (5004032)	131 (5004050)	215 (5004068)	480 (5004086)	600 SV-65S-G50/G65-0400
0.50	40 (5004015)	107 (5004033)	147 (5004051)	260 (5004069)	610 (5004087)	750 SV-65S-G50/G65-0500
0.60	43 (5004016)	117 (5004034)	161 (5004052)	280 (5004070)	650 (5004088)	800 SV-65S-G50/G65-0600
0.70	47 (5004017)	126 (5004035)	174 (5004053)	295 (5004071)	690 (5004089)	865 SV-65S-G50/G65-0700
0.80	50 (5004019)	135 (5004037)	186 (5004055)	320 (5004073)	710 (5004091)	SV-65S-G50/G65-0800
0.90	55 (5004021)	144 (5004039)	196 (5004057)	360 (5004075)	(5004093)	SV-65S-G50/G65-0900
1.00	60 (5004023)	152 (5004041)	208 (5004059)	(5004071)	(5004095)	SV-65S-G50/G65-1000
1.20	62 (5004025)	166 (5004043)	229 (5004061)	(5004079)	(5004097)	SV-65S-G50/G65-1200
1.40	66 (5004026)	180 (5004044)	247 (5004062)	(5004080)	(5004098)	SV-65S-G50/G65-1400
1.60	70 (5004027)	190 (5004045)	260 (5004063)	(5004081)	(5004099)	SV-65S-G50/G65-1600

**Opening pressure 0.05–2.0 MPa. Can be ordered with optional opening pressure within the given intervals.

**ART. NO. refers to valve with seal material of fluorinated rubber (FPM/FKM).